



High Gloss Enamel

DATA SHEET



High Gloss Enamel

Description:

Panda High Gloss Enamel is a renowned brand of Elite Class Synthetic Enamels. The enamel with a colorful history of over 50 years, is well known and extensively used for brushing and spraying application in almost every conceivable situation which requires a resilient long-lasting finish.

Panda High Gloss Enamel is a Universal Enamel for mild steel, wood and concrete.

Surface Preparation and Application:

Proper surface preparation is the key to success in paints application Panda High Gloss Enamel is a finishing paint, and should be applied on properly cleaned and primed surface.

Technical Data:

Type	Single Pack
Composition	Light fast weather resistant pigments dispersed in high quality synthetic resins, selected for their excellent gloss and gloss retention properties.
Colors	White, Black and all shades exhibited in our shade card.
Application	Brush / Spray or Roller
Drying Time	a) Surface Dry: Maximum one Hour. b) Hard Dry : 24 Hours c) Recoat : 24 Hours
Average Spreading Rate	9 - 11 sq. m per liter.
Dry Film Thickness	20 ± microns per coat.
Number of Coats	Minimum 2.
Gloss	Full Gloss.
Primer	Panda Paint Red Oxide, Red Lead Primer or any other alkyd-based primer considered appropriate.
Thinner	Panda Mixing Thinner or white spirit and petrol.
Packing	9l, 3.64, 14.56 Liter.
Storage Stability	One Year when stored properly in original sealed container at 15 to 35 C.