



Red Lead Primer

DATA SHEET



Red Lead Primer

Description:

Panda Red Lead Primer is an anticorrosive primer for all steel surfaces, it is a good barrier against severe weather conditions.

On account its lead content, this primer is recommended for brush/roller application. It is in ready to use condition, however if thinning is required slight quantity of Mixing Thinner can be added.

Panda Red Lead Primer is of air-drying quality. It is flexible and has excellent corrosion resistance in severe weathering conditions. These weathering qualities are highly desirable for protection of structural steel.

Uses:

Beams, Gates, Storage Tanks, Pipelines, Bridges and similar structures where good resistance to corrosion is required, surface preparation is marginal and in adverse application conditions. It can also be using an ant termite treatment for wooden structures.

Technical Data:

Type	Single Pack
Colors	Orange.
Application	Brush/roller.
Drying Time	a) Surface Dry : Within 30 Minutes. b) Recoat ability : 16 hours c) Hard Dry : 24 hours
Average Spreading Rate	9 – 11 square meter per liter
Dry Film Thickness	35 ± 5 microns.
Number of Coats	Two.
Finish and Gloss	Smooth – Matt.
Volume Solids	70 ± 2%.
Top Coat	Panda High Gloss Enamel.
Thinner	Panda Mixing Thinner.
Packing	.9l, 3.64, Liter.
Storage Stability	One year when stored properly in original sealed container at 15 to 35°C