



Super Emulsion

DATA SHEET



Super Emulsion

Description:

A plastic Satin emulsion finish is obtained with Panda Vinyl Emulsion. This product is an excellent combination of quality finish like an economy Vinyl Emulsion Paint. Panda Vinyl Emulsion is an ideal finish for protection and decoration of living rooms, kitchens and bath rooms. It is resistant to water and sunlight and is suitable for interior Finish. Panda Vinyl Emulsion is supplied in many pleasant and attractive shades, the pastel shades of P.V.E. can be intermixed and give an infinite variety of very attractive tones.

Surface Preparation and Application:

The concrete surface should be dry, and efflorescence in the form of white powder should be thoroughly cleaned by washing and later surface should be prepared with grinding stone and sand paper.

Technical Data:

Viscosity @ 25°C	Paste like consistency – 38 poises minimum.
Binder Type	Copolymer Vinyl Emulsion.
Colors	White and all shades exhibited on our P.V.E. shade card.
Drying Time	a) Surface Dry: 20-30 Minutes. b) Recoat : 1 Hour c) Hard Dry : 2 Hours.
Dry Film Thickness	25-30 microns.
Application	Brush and Roller
Coats Recommended	2-3 Coats
Finish And Gloss	Smooth and Flat
Average Spreading Rate	Gives complete finished area 25-30 Sq. Meters per 5 Kg. in 2-3 coats
Thinner	Water
Storage Stability	One Year when stored properly in original sealed container.
Packing	1.4 kgs, 5.625kgs and 22.5kgs