



Weather Shield For 100% Acrylic Based

DATA SHEET



Weather Shield For 100% Acrylic Based EXTERIOR MASONRY COATING

Description:

A high-build breathing exterior masonry coating with water repellency properties.

Panda Weather Shield is an absolutely new exterior coating. It will continue to look clean and fresh when other types of 'Long Lasting' finishes begin to fade, chip, flake or crack, as it has been formulated specially to fight the vagaries of weather, smog and other environmental factors hence 'WEATHER SHIELD';

Panda Weather Shield is a balanced formulation, based on a blend of weather resisting pigments and acrylic dispersion.

Panda Weather Shield has been applied on exteriors of various buildings, such as apartments in particular facing sea breeze, hospitals, factories, mosques, hotels, office blocks and other such construction.

Surface Preparation and Application:

Proper surface preparation and skillful application plays significant role to achieve required results. On new surface brush-off dust and loose adherent concrete. On old previously painted surfaces remove chipped flakes, mouldid algae and other contaminants; cracks and chipped plaster should be repaired with cement/sand mixture and properly cured before painting.

Technical Data:

Consistency	Thixotropic fluid.
Binder Type	Modified Acrylic Binder.
Colors Available	White and as per Weather Shield shade card.
Application	Brush, Roller
Spreading Rate	13-15 Sq. m ² /liter/coat.
Drying Time	a) Surface Dry : 15-20 Minutes. b) Hard Dry : 1 Hours c) Recoat : 4 Hours
Number of Coats	2 - 3 coats.
Finish	Smooth flat finish.
Thinner	Clean water.
Storage Stability	1 year under proper storage condition in original sealed container.

Packing	1, 4 liters and 16 liters.
Storage Stability	One Year when stored properly in original sealed container.
Packing	1.5 kgs, 3kgs, 6kgs and 24 kgs

